

Passenger Entrances & Replacement Panels

UL FEATURES FOR 1 1/2 HOUR DOORS

CENTER OPENING

| Speed | Sill Width | Sill Projection | Max Opening Width | Max Opening Height |
|-------|------------|-----------------|---------------------------|--------------------|
| 1 | 4 in | 5 in | 96 in (Masonry & Drywall) | 120 in |
| 2 | 5 1/2 in | 6 1/2 in | 96 in (Drywall) | |
| | | | 144 in (Masonry) | |

SIDE OPENING


| Speed | Sill Width | Sill Projection | Max Opening Width | Max Opening Height |
|-------|------------|-----------------|--------------------------|--------------------|
| 1 | 4 in | 5 in | 48 in (Masonry, Drywall) | 120 in |
| 2 | 5 1/2 in | 6 1/2 in | 96 in (Masonry, Drywall) | |
| 3 | 7 in | 8 in | 96 in (Drywall) | |
| | | | 144 in (Masonry) | |

Standard Features

- ✓ Passenger Entrances are 1-1/2 hour fire rated UL labeled
- ✓ Door Panels: 16 Gauge Face Sheet, 16 Gauge Back Sheet
- ✓ Panel Thickness: 1.25 in, 1.5 in, 2.75 in
- ✓ Two Door Guides and one 14 Gauge safety retainer per panel
- ✓ Standard GAL equipment mounting provisions are included
- ✓ Frames: 16 Gauge Sheet with a 2" square profile (bolted, welded, or welded and mitred)
- ✓ Fascia: 16 Gauge Sheet with maximum 12 ft floor height maximum (blind fascia for skipped or bypassed floors are non-standard)
- ✓ Standard Header and Strut Design: 12 Gauge including Hoistway Material (header, struts, etc.)
- ✓ Sill Construction: Aluminum (standard), Nickel Silver, Stainless Steel or Bronze are optional
- ✓ Panel and Frame Finishes: Powder Coated, Stainless, Bronze

Optional Features

- ✓ Complete Stainless Steel Construction (1-1/2 hour fire rated UL labeled) with zinc plated hardware
- ✓ Glass Entrances / Car Doors (UL Label not required)
- ✓ Vision Panel (3 in x 10 in)
- ✓ Sound Deadener: Antivibe DL-10
- ✓ Projected Transom: US only. 48 in wide x 36 in tall (Oversize: 48 in wide x 120 in tall, Frame height with transom 204 in Max)
- ✓ Zero Clearance Frame: Depth Min - 6 in Max - 8 in, 16 Gauge, plain, stainless, galvanized, galvanealed (swing door by others)
- ✓ Cutouts
 - ✓ Jamb - 3 in x 13.375 in
 - ✓ Transom - 6 in x 24 in
- ✓ Min and Max wall thickness
 - ✓ Min 6 in (Wall - 4 in)
 - ✓ Over 13 in additional drywall mounting



THE PEELLE COMPANY
34 E. Main Street, #372, Smithtown, NY 11787

THE PEELLE COMPANY LTD
195 Sandalwood Parkway West, Brampton, ON L7A 1J6

1 800 787 5020
1 905 846 4545

SALES@PEELLEDOR.COM
PEELLEDOR.COM